



Zebra® 105SL™

Thermal, On-Demand, All-Metal Bar
Code Printer

Serious about bar coding? Here's the choice of experience.

The 105SL combines enhanced memory, processing capacity, and features with rugged and reliable all-metal construction. Proven platform longevity plus fast processing and print speed make it the choice of experienced users who value reliability, productivity, consistent print quality, network compatibility, and superior service and support.

Cutting-Edge Network Connectivity

The 105SL offers flexible connectivity solutions including ZebraNet® Wireless Print Server to free you to move or reconfigure the printer without costly recabling, plus ZebraNet 10/100 Print Server, which offers a complete wired solution when using 10Base-T, 100Base-TX, and fast Ethernet 10/100 auto-switching networks. And with Zebra advanced printer management, gain the efficiency and the ease of centralized monitoring and control of your Zebra printers and ZebraNet print servers.

The 105SL is ideal for moderate- to high-volume printing applications (including distributed, batch, or single format) in:

- Manufacturing and compliance labeling
- Logistics and inventory control
- Product identification marking
- Work in process



105SL



Specifications at a Glance*

MEDIA CHARACTERISTICS

Maximum label and liner length
39"/991 mm

Maximum label and liner width
.79"/20 mm to 4.52"/115 mm

Maximum roll outer diameter (O.D.)
8"/203 mm

Core inner diameter (I.D.)
3"/76 mm

Media thickness
.003"/.076 mm to .012"/.305 mm

Media types
Roll-feed, die-cut, continuous, fanfold, tags, tickets
For optimum print quality and printer performance,
use Genuine Zebra Supplies.

RIBBON CHARACTERISTICS

Outside diameter
3.2"/81.3 mm

Standard length
984'/300 m to 1,476'/450 m

Ratio
2:1 and 3:1 media roll to ribbon ratio

Width
.79"/20 mm to 4.5"/114 mm

Ribbon setup
Ribbon wound ink side out
Ribbon is recommended to be at least as wide as media.

Core inner diameter (I.D.)
1"/25.4 mm

OPERATING CHARACTERISTICS

Environmental
Operating Temp. 41° F/5° C to 104° F/40° C
Storage/Environ. -40° F/-40° C to 140° F/60° C
Operating Humidity 20-85% non-condensing
Storage Humidity 5-85% non-condensing

Electrical
Universal power supply with factor correction
90-264 VAC; 48-63 Hz

Agency Approvals
UL 1950; CISPR 22 (Class B); CSA 950; IEC 950;
801-2, -3 and -4 standards; Canadian Doc.
(Class A); FCC (Class A); CE compliance

PHYSICAL CHARACTERISTICS

Width: 11.2"/283 mm
Height: 15.5"/394 mm
Depth: 19.5"/495 mm
Weight: 55 lbs./25 kg
Shipping weight: 63 lbs./29 kg

RELATED PRODUCTS

Options and Accessories
300 dpi printhead
Full width cutter with orderable catch tray
Internal rewind spindle
Peel/liner rewind (for print-and-apply)
Reflective media sensor
Fanfold bin

ZEBRALINK™ SOLUTIONS

Software
ZebraDesigner™ Pro
ZebraNet™ Bridge Enterprise
ZebraNet Utilities v 7.0
Zebra Universal Driver
European and Asian font sets

Networking
ZebraNet 10/100 Print Server (internal or external)
ZebraNet Wireless Print Server
ZebraNet PrintServer II (internal or external)
Twinx and coax interfaces (internal)

Firmware
ZPL II®—Universal language for Zebra printers.
Simplifies label formatting and enables format compatibility with other Zebra printers.
APL™—In many cases, Zebra's Alternate Programming Language allows integration of the 105SL printer into mixed printer environments without format re-programming (available in 203 dpi printers only). For additional information on Zebra's APL products please visit www.zebra.com.
Web View—Enables you to connect and control your bar code printer's Web interface using a common Web browser.
Alert—Printers equipped with ZebraNet print servers will notify you via any email-enabled, wired, or wireless device to minimize downtime.

COMMUNICATION AND INTERFACE CAPABILITIES

Centronics® RS-232 RS-422*, and RS-485* serial ports; IEEE 1284 bi-directional parallel

BAR CODE SYMBOLOGIES

Linear Bar Codes
Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, RSS

2-Dimensional
Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, MicroPDF417, RSS

FONTS AND GRAPHICS

Fonts and Character Sets
Standard Fonts: 7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
Sets: IBM® Code Page 850 International character set
Contains UFST® from Agfa Monotype Corp.

Graphic Features
Supports user-defined fonts and graphics—including custom logos
ZPL II drawing commands—including boxes, circles and diagonal lines

A tough steel housing, metal interior components, and an extruded metal printhead mechanism contribute to the 105SL's reliability in industrial environments.

STANDARD FEATURES

Print methods: Thermal transfer or direct thermal
Construction: Steel frame and cabinet with metal interior components
Multi-level Element Energy Equalizer™ (E³) for superior print quality
Fast 32-bit processing
Selectable print speeds up to 8"/second
Transmissive media sensor
Standard 2-line, 16-character LCD control panel

PRINTER SPECIFICATIONS

Resolution
203 dpi/8 dots per mm;
300 dpi/12 dots per mm (optional)

Memory
Standard: 6 MB SDRAM; 4 MB Flash
Optional: Available up to 256 MB (PCMCIA card or CompactFlash)

Print Width
Width: 4.09"/104 mm

Print Length with 203 dpi:
106"/2,692 mm (with standard memory)

Print Length with 300 dpi (optional):
65"/1,651 mm (with standard memory)

Print Speed
8"/203 mm per second (203/300 dpi)

Media Sensors
Transmissive
Reflective (optional)

*Specifications subject to change without notice.
©2005 ZIH Corp. ZebraDesigner, ZebraLink, ZebraNet, APL, Element Energy Equalizer, and all product names and numbers are Zebra trademarks and Zebra, ZebraNet, E³ and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Centronics is a registered trademark of Centronics Data Computer Corporation. CG Triumvirate is a trademark of Agfa Division, Miles Inc. IBM is a registered trademark of International Business Machines Corporation. UFST is a registered trademark of Agfa Monotype Corporation. All other trademarks are the property of their respective owners.

HEADQUARTERS Zebra Technologies International, LLC **T:** +1 847 793 2600 or +1 800 423 0442 **F:** +1 847 913 8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. **WEB:** www.zebra.com

OTHER LOCATIONS **USA:** California, Rhode Island, Wisconsin **EUROPE:** France, Germany, Italy, Netherlands, Poland, Spain, Sweden, United Kingdom **ASIA-PACIFIC:** Australia, China, Japan, Singapore, South Korea
LATIN AMERICA: Florida (USA), Mexico **AFRICA/MIDDLE EAST:** South Africa, United Arab Emirates



An ISO 9001 registered company
GSA#: GS-35F-0268N
©2005 ZIH Corp. Printed in U.S.A.
#11341L Rev. 13 (7/05) 10M

Barcodes Inc. is a leading provider of barcode, mobile computing and RFID solutions. Headquartered in Chicago, we have been in business since 1994. We have experienced rapid growth every year, thanks to our focus on the customer and our flexible, solution-oriented approach to our customers' needs. We are product experts with deep experience in field mobility, healthcare, retail and warehouse application solutions. We proudly work with over two-thirds of the Fortune 500 list as well as thousands of small and medium-sized businesses.



Dedicated Account Team

A typical Account Team consists of an Account Manager, an onsite Systems Integrator, plus technical resources in specialty areas like Enterprise Mobility, POS systems or Wireless equipment. An Account Manager is the Primary Point of Contact for your business. Your Account Manager makes it a priority to get to know you, your company and all your needs.



Technical Advice and Solution Expertise

We have deep experience installing and supporting data collection and mobility systems for clients in multiple industries and in government. Our Account Managers are industry experts with superior experience in project management. They work hard to understand your business so they can work with our technical experts to make effective recommendations. They will see your project through from the initial solution to implementation and beyond.



Logistical Excellence

Priority orders are completed within minutes and ship the same day. 99.9% of all orders ship on time. We utilize a network of warehouses across the U.S. to ensure that you get what you need, when you need it.



Online resources

Our online resources are intended to make your job easy. We offer secure online ordering, detailed product information, industry news, specials, chat and account management tools, so you can always get the information you need.



Incredible Value and the Broadest Product Offering Available

Our purchasing power means big savings for you. In addition, we are an authorized value-added reseller for all of the trusted manufacturers in the industry and a premier partner of all of the top brands. This access allows us to offer the broadest product offering, excellent prices and the product support you deserve.

CALL US 1.800.351.9962

VISIT US ONLINE
www.barcodesinc.com

Barcodes, Inc, 218 S Wabash Avenue, Suite 500, Chicago IL 60604
Phone 800.351.9962 Fax 312.212.1800 www.barcodesinc.com